

NEXUS CT® POINT-OF-USE

MODELS

HOT & COLD: 360125 - BLACK

Features

- Appliance styling
- 11" dispensing height
- Lighted spout and dispensing area
- Hot & cold temperature indicator
- Safety lock function for hot & cold water
- Fast flow electronic dispensing
- Accu-Temp - Serves water at the proper temperature every time
- Stay-Cool - Keeps the residual water in the cold waterway chilled and ready to serve
- SIP enhanced sanitization sanitizes cold reservoir, waterways and spout
- i-Boil - Increases the hot water temperature to just under boiling - perfect for coffee, teas, noodles, etc.
- Dual mechanical float for reliability
- Room for filter inside
- Available in black or white
- UL certified

Models

H&C: GCB 215i-SIP, GCW 215i-SIP



GCB 215i-SIP



GCW 215i-SIP



Available in white soon

| Power | |
|--|-----------------------------|
| Voltage (V) | 115, 220, 100 |
| Frequency (Hz) | 50/60 |
| Power Consumption | 4.83A / 547W / 115V |
| Cold Power Consumption | 1.51A / 109.4W / 115V |
| Hot Power Consumption | 3.87A / 449W / 115V |
| ES (KWH/24hrs) | 0.719 |
| % lower than ES Standard | 40% |
| Hot Water System | |
| Avg. Hot Water Temp at nozzle @ 75°F ambient(Before/After On) | 173.53°F / 188.5°F |
| Hot water ARI Rating | 37 6 oz > 165°F +/-10% |
| Hot Thermostat / Heat Limiter | 203°F +/- 5.5°F |
| Hot Thermostat / Thermister Cycle | 172° - 190°F |
| i-Boil Set Point | 192°F |
| Avg. Temp of i-Boil at nozzle @ 75°F ambient (After On) | 202.83°F |
| Hot Water Flow Rate | 1.3 oz/sec |
| Hot Water Flow Rate (ml per sec)w/Accu-Temp delay | 1.17 oz/sec |
| Hot Tank Size (L) | 1.4L |
| Heat Band Wattage | 450W |
| Cold Water System | |
| Avg. Cold Water Temp at nozzle @ 75°F ambient(Before/After ON) | 46.03° / 40.9° F |
| Cold Water ARI Rating | 24 5oz < 50°F +/-10% |
| Cold Thermostat Set Point | 45°F +/-8°F |
| Cold Water Flow Rate | 1.35 oz/sec |
| Cold Water Flow Rate (oz per sec)w/ Accu-Temp delay | 1.22 oz/sec |
| Cold Tank Size / Usable Volume / Below Baffle Cold Water (Gal) | 0.94 / 0.7 / 0.35 |
| Weights and Measurements | |
| Net Weight (Lbs) | 35.3 |
| Gross Weight (Lbs) | 38.4 |
| Cooler Dimensions / Boxed Dimensions WxDxH (inch) | 14.2x18.3x17.3 / 15x18x18.9 |
| Container Load (20') | 308 |
| Container Load (40') | 612 |
| Container Load (40' HC) | 785 |
| Container Load (45' HC) | 885 |
| Certifications | UL |