

ALPINE ST5000

Refrigerated Glass Front Merchandiser



The Alpine ST5000 glass front refrigerated food & beverage merchandiser provides the largest dispensing capability with class leading energy efficiency. Vend sodas, juices, milk, yogurts, and other foods best served cold from one versatile package.



- ENERGY STAR® Rated
- Advanced styling & touch screen interface options
- Americans with Disabilities Act (ADA) compliant
- Programmable health safety by selection, range or row
- Unmatched beverage options
- Motor pairing capable
- Single & dual coil options
- Large LED lighted point of sale window
- Energy efficient LED lighting
- Steel snack tray option
- New self cleaning condenser coil with reverse on startup fan






ALPINE ST5000 Refrigerated Glass Front Merchandiser



Shown in black with kick panel option.

Sample Configuration



Alpine ST5000

Selections

Canacity

Electrical

Requirements

Refrigeration

Dimensions Shipping Weight

Options

Standard Features

Selection Pricing

Payment Systems

Data Communication

Up to 60 items

DFX/UCS

Varies with tray configuration

Individual from \$0 to \$9,999.95

All Industry standard MDB compatible devices

Super 1/3 HP, R-134a or R-513a Closed System

9 Select Can & Bottle Trays, Door Switch

Features

- **Optional touch screen interface**
 - Built-in, full color 7" LCD screen replaces traditional keypad & display
- **ENERGY STAR® Rated**
- Attractive styling bezel with point of sale window
- **Americans with Disabilities Act Compliant**
- Standard peripheral opening for additional payment or POS systems
- Standard lighted keypad with Braille identification
- MDB support for all industry standard devices including cash, coin, debit and credit systems
- **DEX data output support**
- Fully integrated controller with sales and accounting features:
 - Price setting by selection, row or machine
 - Free vend and Combo vend modes
 - Flexible space to selection setting
 - Time of day discounting
 - Time of day shutdown modes for energy savings and controlled vend times
 - Programmable point of sale messages
 - Programmable coupon and token values
 - Coin and bill rejection rate counts
 - Accountability display by selection, row or machine
 - Talker device support for sight impaired (Talker not included)
- Motor pairing capable

Domestic: 115 VAC/60Hz, 9.5 AMPS International: 230 VAC/50Hz, 4.8 AMPS; With

Heated Glass: 115 VAC/60Hz 10.5 AMPS. International: 230 VAC/50Hz 5.2 AMPS.

Heated Glass, iCart Touch Screen Interface, inDEX Tool, 6th Tray, Dual Helix, Motor

Pairing, 10 Select Can/Bottle Tray, High Capacity Can Tray, Custom Helix and Tray

Height 72"(183 cm) Width 41" (104 cm) Depth 38" (97 cm)

*791 lbs. (358.8 kg) *Varies with tray configuration and options. GVC2 Controller, LED Lighting, iVend® Sensor System, Delivery Assist Box

- Proven operating environment
 - High: 100°F (38°C) @ 90% RH
- Reverse on startup condenser fan
- 2 year warranty contact USI for complete details



Energy Efficient

- Uses only 4.2 Kwh/day @ 75°F (24°C), 45% RH based on refrigerating 34.6 cu.ft. of space
- Low-E Argon filled insulated glass
- **LED lighting**
- Thickest foaming on the market with Eco-friendly **BASF Autofroth® foaming process**
- **Balanced airflow design**
- **Energy saving programmable shutdown modes**
- **Eco-friendly refrigeration system**

Adjustable Food **Selections**

Quickly re-configurable to almost any package size. Full selection (5-3/4"W) 3/4 selection (4-5/16"W) Candy selection (2-7/8"W



Standard Delivery Assist for Full ADA Compliance

Product is delivered at 15" via manual lift and actuated by product door entry.



CART

Optional iCart Touch Screen Interface

Enhances consumer purchase experience. Communicates purchase information & messages to consumer.



figreenlite*

Optional Cashless

Greenlite Cashless accepts credit, debit & mobile payments with valuable telemetry and machine management tools.



Versatile Steel **Beverage Trays**

Hold up to 60 canned or bottle beverages and come in 9 select or optional 10 select versions.











